

HIT-RE 500-SD

Safety information for 2-Component-products

Date of issue: 08/11/2017

Revision date: 08/11/2017

Supersedes: 17/05/2017

Version: 9.1

SECTION 1: Kit identification

1.1 Product identifier

Product name HIT-RE 500-SD
Product code BU Anchor



1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti (Israel) Ltd.
6 Ravnitsky St. Ind. Zone Sgula
P.O. Box 2650
49125 Petach Tikva - Israel
T +972 3 930 4499 - F +972 3 930 2095
info@hilti.co.il

SECTION 2: General information

Storage Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3: Kit contents

Classification of the Product

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Corr. 1A H314
Skin Sens. 1 H317
Repr. 1B H360F
Aquatic Chronic 2 H411

Full text of hazard classes and H-statements : see section 16

Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS05



GHS07



GHS08



GHS09

Signal word (CLP)

Danger


HIT-RE 500-SD

Kit Safety Information Sheet

Hazardous ingredients	Epoxy resin, Amines
Hazard statements (CLP)	H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H360F - May damage fertility. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	P280 - Wear eye protection, protective clothing, protective gloves. P262 - Do not get in eyes, on skin, or on clothing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P302+P352 - IF ON SKIN: Wash with plenty of water/...

Additional information

2-component-foilpack, contains:
 Component A: Epoxy resin, Reactive diluent, inorganic filler
 Component B: Amine hardener, inorganic filler



Name	General description	Quantity	Unit	Classification according to Regulation (EC) No. 1272/2008 [CLP]
HIT-RE 500-SD, A		1	pcs (pieces)	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 1B, H360F Aquatic Chronic 2, H411
HIT-RE 500-SD, B		1	pcs (pieces)	Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412

SECTION 4: General information

No data available

SECTION 5: Safe handling advice

General measures	Spilled material may present a slipping hazard
Environmental precautions	Prevent entry to sewers and public waters Notify authorities if liquid enters sewers or public waters Avoid release to the environment. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.
Storage conditions	Protect from sunlight. Store in a well-ventilated place.
Technical measures	Comply with applicable regulations
Precautions for safe handling	Wear personal protective equipment Avoid contact with skin and eyes Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work Avoid contact during pregnancy/while nursing
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation Mechanically recover the product On land, sweep or shovel into suitable containers Store away from other materials.
For containment	Collect spillage.
Incompatible materials	Sources of ignition

HIT-RE 500-SD

Kit Safety Information Sheet

Incompatible products	Direct sunlight Strong bases Strong acids
-----------------------	---

SECTION 6: First aid measures

First-aid measures after eye contact	Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist
First-aid measures after ingestion	Drink plenty of water Do not induce vomiting Rinse mouth. Immediately call a POISON CENTER/doctor
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	Wash with plenty of water/... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
First-aid measures general	Never give anything by mouth to an unconscious person If you feel unwell, seek medical advice (show the label where possible)
Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after eye contact	Causes serious eye damage.
Symptoms/effects after inhalation	May cause an allergic skin reaction.
Other medical advice or treatment	Treat symptomatically

SECTION 7: Fire fighting measures

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

SECTION 8: Other information

No data available

HIT-RE 500-SD, B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 19/05/2017

Revision date: 19/05/2017

Supersedes: 14/12/2015

Version: 8.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	Mixture
Product name	HIT-RE 500-SD, B
Product code	BU Anchor

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec	For professional use only
Use of the substance/mixture	Composite mortar component for fasteners in the construction industry

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Hilti (Israel) Ltd.
6 Ravnitsky St. Ind. Zone Sgula
P.O. Box 2650
49125 Petach Tikva - Israel
T +972 3 930 4499 - F +972 3 930 2095
info@hilti.co.il

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906310 - F +49 8191 90176310
anchor.hse@hilti.com

1.4. Emergency telephone number

Emergency number	Schweizerisches Toxikologisches Informationszentrum – 24h Service +41 44 251 51 51 (international) +972 3 930 4499
------------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 1A	H314
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS05



GHS07

HIT-RE 500-SD, B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Signal word (CLP)	Danger
Hazardous ingredients	m-Xylylenediamine
Hazard statements (CLP)	H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	P280 - Wear eye protection, protective clothing, protective gloves. P262 - Do not get in eyes, on skin, or on clothing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
m-Xylylenediamine	(CAS-No.) 1477-55-0 (EC-No.) 216-032-5 (REACH-no) 01-2119480150-50	25 - 40	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 Skin Sens. 1B, H317 Aquatic Chronic 3, H412

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	Wash with plenty of water/.... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist.
First-aid measures after ingestion	Drink plenty of water. Do not induce vomiting. Rinse mouth. Immediately call a POISON CENTER/doctor.

HIT-RE 500-SD, B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
--	--

5.3. Advice for firefighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
6.1.1. For non-emergency personnel	
Emergency procedures	Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.

6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

HIT-RE 500-SD, B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact during pregnancy/while nursing.

Hygiene measures Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures Comply with applicable regulations.

Storage conditions Protect from sunlight. Store in a well-ventilated place.

Incompatible products Strong bases. Strong acids.

Incompatible materials Sources of ignition. Direct sunlight.

Storage temperature 5 - 25 °C

Heat and ignition sources Keep away from heat and direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls

Personal protective equipment Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

Hand protection Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4	EN 374

Eye protection Wear security glasses which protect from splashes

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection Wear suitable protective clothing



Environmental exposure controls Avoid release to the environment.

Consumer exposure controls Avoid contact during pregnancy/while nursing.

Other information Do not eat, drink or smoke during use.

HIT-RE 500-SD, B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	red.
Odour	Amine-like.
Odour threshold	No data available
pH	11.5
Relative evaporation rate (butylacetate=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Non flammable
Vapour pressure	No data available
Relative vapour density at 20 °C	No data available
Relative density	No data available
Density	1.41 g/cm ³ DIN EN ISO 1183-3
Solubility	insoluble in water.
Log Pow	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	50 Pa.s HN-0333
Explosive properties	No data available
Oxidising properties	No data available
Explosive limits	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive vapours.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

HIT-RE 500-SD, B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide. Corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

m-Xylylenediamine (1477-55-0)	
LD50 oral rat	1090 mg/kg
LD50 oral	660 mg/kg
LD50 dermal rat	> 3100 mg/kg
LD50 dermal	2000 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	1.34 mg/l/4h

Skin corrosion/irritation	Causes severe skin burns and eye damage. pH: 11.5
Serious eye damage/irritation	Causes serious eye damage. pH: 11.5
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
Reproductive toxicity	Not classified
Additional information	Based on available data, the classification criteria are not met
STOT-single exposure	Not classified
Additional information	Based on available data, the classification criteria are not met
STOT-repeated exposure	Not classified
Additional information	Based on available data, the classification criteria are not met
Aspiration hazard	Not classified
Additional information	Based on available data, the classification criteria are not met

HIT-RE 500-SD, B	
Viscosity, kinematic	35460.9929078 mm ² /s

Potential adverse human health effects and symptoms	Based on available data, the classification criteria are not met.
---	---

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Harmful to aquatic life with long lasting effects.
Acute aquatic toxicity	Not classified
Chronic aquatic toxicity	Harmful to aquatic life with long lasting effects.

m-Xylylenediamine (1477-55-0)	
LC50 fish 1	75 mg/l
LC50 other aquatic organisms 1	20.3 ppb
EC50 Daphnia 1	15 mg/l
LOEC (chronic)	15 mg/l
NOEC (acute)	10.5 mg/kg
NOEC (chronic)	4.7 mg/l

HIT-RE 500-SD, B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

NOEC chronic crustacea	4.7 mg/l
------------------------	----------

12.2. Persistence and degradability

HIT-RE 500-SD, B	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

HIT-RE 500-SD, B	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

HIT-RE 500-SD, B	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

12.6. Other adverse effects

Additional information: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to Avoid release to the environment, Refer to manufacturer/supplier for information on recovery/recycling.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IATA / IMDG / RID

Other information: No supplementary information available

ADR Regulatory status: Regulated
 IMDG Regulatory status: Regulated
 IATA Regulatory status: Regulated
 RID Regulatory status: Regulated

ADR	IMDG	IATA	RID
14.1. UN number			
3259	3259	3259	3259
14.2. UN proper shipping name			
AMINES, SOLID, CORROSIVE, N.O.S.	AMINES, SOLID, CORROSIVE, N.O.S.	Amines, solid, corrosive, n.o.s.	AMINES, SOLID, CORROSIVE, N.O.S.
Transport document description			
UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (m-Xylylenediamine), 8, II, (E)	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (m-Xylylenediamine), 8, II		
14.3. Transport hazard class(es)			
8	8	8	8

HIT-RE 500-SD, B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	RID
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available			

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	C8
Special provisions (ADR)	274
Limited quantities (ADR)	1kg
Packing instructions (ADR)	P002, IBC08
Mixed packing provisions (ADR)	MP10
Orange plates	



Tunnel restriction code (ADR)	E
-------------------------------	---

- Transport by sea

Special provisions (IMDG)	274
Limited quantities (IMDG)	1 kg
Packing instructions (IMDG)	P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A
Stowage and segregation (IMDG)	Separated from' acids.
MFAG-No	154

- Air transport

PCA packing instructions (IATA)	859
PCA max net quantity (IATA)	15kg
CAO packing instructions (IATA)	863
Special provisions (IATA)	A3

- Rail transport

Special provisions (RID)	274
Limited quantities (RID)	1kg
Packing instructions (RID)	P002, IBC08
Carriage prohibited (RID)	No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

HIT-RE 500-SD, B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information None.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.

SDS_EU_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

HIT-RE 500-SD, A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 19/05/2017

Revision date: 19/05/2017

Supersedes: 14/12/2015

Version: 9.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	Mixture
Product name	HIT-RE 500-SD, A
Product code	BU Anchor

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec	For professional use only
Use of the substance/mixture	Composite mortar component for fasteners in the construction industry

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Hilti (Israel) Ltd.
6 Ravnitsky St. Ind. Zone Sgula
P.O. Box 2650
49125 Petach Tikva - Israel
T +972 3 930 4499 - F +972 3 930 2095
info@hilti.co.il

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906310 - F +49 8191 90176310
anchor.hse@hilti.com

1.4. Emergency telephone number

Emergency number	Schweizerisches Toxikologisches Informationszentrum – 24h Service +41 44 251 51 51 (international) +972 3 930 4499
------------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 1C	H314
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Reproductive toxicity, Category 1B	H360F
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS05



GHS07



GHS08



GHS09

HIT-RE 500-SD, A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Signal word (CLP)	Danger
Hazardous ingredients	Bisphenol-A-Epichlorhydrin Epoxy resin Average MW < 700 ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol ; Reaction products of hexane-1,6-diol with 2-(chloromethyl); 1,3 Propanediol, 2 ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane
Hazard statements (CLP)	H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H360F - May damage fertility. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	P280 - Wear eye protection, protective clothing, protective gloves. P262 - Do not get in eyes, on skin, or on clothing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P302+P352 - IF ON SKIN: Wash with plenty of water/...

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Bisphenol-A-Epichlorhydrin Epoxy resin Average MW < 700	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26	25 - 40	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	(CAS-No.) 9003-36-5 (EC-No.) 500-006-8 (REACH-no) 01-2119454392-40	10 - 25	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Reaction products of hexane-1,6-diol with 2-(chloromethyl)	(CAS-No.) 933999-84-9 (EC-No.) 618-939-5 (REACH-no) 01-2119463471-41	10 - 25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412
1,3 Propanediol, 2 ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane	(CAS-No.) 30499-70-8 (EC-No.) 608-489-8 (REACH-no) 01-2120078341-60	5 - 10	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 1B, H360F Aquatic Chronic 2, H411

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Bisphenol-A-Epichlorhydrin Epoxy resin Average MW < 700	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26	(C >= 5) Eye Irrit. 2, H319 (C >= 5) Skin Irrit. 2, H315

Full text of H-statements: see section 16

HIT-RE 500-SD, A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Assure fresh air breathing. Allow the victim to rest.
First-aid measures after skin contact	Gently wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Drink plenty of water. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after skin contact	Causes skin irritation.
Symptoms/effects after eye contact	Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
--	--

5.3. Advice for firefighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
6.1.1. For non-emergency personnel	
Emergency procedures	Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.

HIT-RE 500-SD, A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Skin and body protection



Wear suitable protective clothing

Environmental exposure controls

Avoid release to the environment.

Consumer exposure controls

Avoid contact during pregnancy/while nursing.

Other information

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	Light grey.
Odour	characteristic.
Odour threshold	No data available
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Non flammable
Vapour pressure	No data available
Relative vapour density at 20 °C	No data available
Relative density	No data available
Density	1.46 g/ml DIN EN ISO 1183-3
Solubility	insoluble in water.
Log Pow	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	43 Pa.s HN-0333
Explosive properties	Product is not explosive.
Oxidising properties	No data available
Explosive limits	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

HIT-RE 500-SD, A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.3. Possibility of hazardous reactions

No additional information available.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

Bisphenol-A-Epichlorhydrin Epoxy resin Average MW < 700 (25068-38-6)	
LD50 oral rat	> 2000 mg/kg (Rat; OECD 420: Acute Oral toxicity – Acute Toxic Class Method; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)	
LD50 oral rat	> 5000 mg/kg bodyweight (Rat; ECHA)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; ECHA)
Reaction products of hexane-1,6-diol with 2-(chloromethyl) (933999-84-9)	
LD50 oral rat	3010 mg/kg
LD50 dermal rat	> 2000 mg/kg

Skin corrosion/irritation	Causes severe skin burns and eye damage.
Serious eye damage/irritation	Causes serious eye damage.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Reproductive toxicity	Based on available data, the classification criteria are not met
Additional information	May damage fertility.
STOT-single exposure	Based on available data, the classification criteria are not met
Additional information	Not classified
STOT-repeated exposure	Based on available data, the classification criteria are not met
Additional information	Not classified
Aspiration hazard	Based on available data, the classification criteria are not met
Additional information	Not classified
Potential adverse human health effects and symptoms	Based on available data, the classification criteria are not met.

HIT-RE 500-SD, A	
Viscosity, kinematic	29452.05479452 mm ² /s

Potential adverse human health effects and symptoms Based on available data, the classification criteria are not met.

HIT-RE 500-SD, A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Toxic to aquatic life with long lasting effects.
Acute aquatic toxicity	Not classified
Chronic aquatic toxicity	Toxic to aquatic life with long lasting effects.

Bisphenol-A-Epichlorhydrin Epoxy resin Average MW < 700 (25068-38-6)

LC50 fish 1	1.2 mg/l (96 h; Oncorhynchus mykiss; Lethal)
EC50 Daphnia 1	1.7 mg/l
LC50 fish 2	2.3 mg/l (96 h; Oncorhynchus mykiss; Nominal concentration)
Threshold limit algae 1	> 11 mg/l (72 h; Scenedesmus sp.)
Threshold limit algae 2	4.2 mg/l (72 h; Scenedesmus sp.)

Reaction products of hexane-1,6-diol with 2-(chloromethyl) (933999-84-9)

LC50 fish 1	30 mg/l
LC50 other aquatic organisms 1	23.1 mg/l
EC50 Daphnia 1	47 mg/l
NOEC (acute)	18 mg/l

12.2. Persistence and degradability

HIT-RE 500-SD, A	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

HIT-RE 500-SD, A	
Bioaccumulative potential	Not established.

Bisphenol-A-Epichlorhydrin Epoxy resin Average MW < 700 (25068-38-6)

BCF other aquatic organisms 1	3 - 31
Log Pow	>= 2.918 (Experimental value; EU Method A.8: Partition Coefficient; 25 °C)
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).

12.4. Mobility in soil

Bisphenol-A-Epichlorhydrin Epoxy resin Average MW < 700 (25068-38-6)	
Surface tension	0.0 587-0.0589,20 °C

12.5. Results of PBT and vPvB assessment

HIT-RE 500-SD, A	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

12.6. Other adverse effects

Additional information	Avoid release to the environment.
------------------------	-----------------------------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to Avoid release to the environment, Refer to manufacturer/supplier for information on recovery/ recycling.
Ecology - waste materials	Avoid release to the environment.

HIT-RE 500-SD, A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 14: Transport information

In accordance with ADR / IATA / IMDG / RID

Other information not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7

ADR Regulatory status: Not regulated
 IMDG Regulatory status: Not regulated
 IATA Regulatory status: Not regulated
 RID Regulatory status: Not regulated

ADR	IMDG	IATA	RID
14.1. UN number			
Not regulated for transport			
14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
Environmentally hazardous substances derogation applies (quantity of liquids ≤ 5 litres or net mass of solids ≤ 5 kg)			
not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7			

14.6. Special precautions for user

- Overland transport

Special provisions (ADR) 375

- Transport by sea

No data available

- Air transport

Special provisions (IATA) A197

- Rail transport

Carriage prohibited (RID) No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

HIT-RE 500-SD, A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no REACH Annex XIV substances

15.1.2. National regulations

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

Section	Changed item	Change	Comments
3.2	Composition/information on ingredients	Modified	

Other information

None.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Repr. 1B	Reproductive toxicity, Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage
H319	Causes serious eye irritation.
H360F	May damage fertility.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS_EU_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product